

Reply to office action dated 12/14/04

**AMENDMENTS TO THE CLAIMS**

Claims pending in the 12/14/04 Office Action: 1-25

Claims pending as a result of this response: 1-25

5      Claims amended in this response: 1, 2, 10, 14, 18, 19, and 20.

Claims cancelled in this response: none

Please amend the claims of the present application as set forth below.

10      1.      (Currently amended) A method comprising:

forming a slot into a substrate and extending between a first substrate surface and a generally opposing second substrate surface, the slot extending along a long axis that extends generally parallel the first surface and being defined, at least in part, by a pair of sidewalls which extend generally parallel to  
15      the long axis; and,

forming at least one bowl-shape into the substrate so that the long axis passes therethrough, the bowl shape being connected to the pair of sidewalls of the slot and defining, at least in part, a terminal region of the slot.

20      2.      (Currently amended) The method of claim 1, wherein said act of forming at least one bowl shape comprises forming at least one bowl shape into [[a]] the first surface of the substrate, and wherein the at least one bowl shape has a width

Reply to office action dated 12/14/04

at the first surface measured generally orthogonal to the long axis that is greater than a width at the first surface measured generally orthogonal to the long axis between the pair of sidewalls.

- 5     3.     (Original) The method of claim 1, wherein said act of forming a slot comprises one or more of: sand drilling, laser machining, and etching.
4.     (Original) The method of claim 1, wherein said act of forming at least one bowl-shape comprises at least one of laser machining and mechanically  
10     removing substrate material.
5.     (Original) The method of claim 1, wherein said acts of forming occur concurrently.
- 15     6.     (Original) The method of claim 1, wherein said act of forming a slot comprises forming the slot so that the two sidewalls are generally orthogonal to the first surface.
7.     (Original) The method of claim 1, wherein said act of forming a slot  
20     comprises forming the slot so that the two sidewalls blend into the first surface.

Reply to office action dated 12/14/04

8. (Original) The method of claim 1, wherein said act of forming at least one bowl shape occurs prior to said act of forming a slot.
9. (Original) A print cartridge comprising, at least in part, a substrate formed  
5 in accordance with the method of claim 1.
10. (Currently amended) A method comprising:  
forming a fluid-feed slot between a first substrate surface and a second  
generally opposing substrate surface, the fluid-feed slot extending along a long  
10 axis which extends generally parallel to the first surface, and having a central  
region and at least one terminal region arranged along the long axis wherein the  
terminal region is wider at the first surface than the central region as measured  
generally orthogonally to the long axis; and,  
blending the slot at the first surface, at least in part, to decrease stress  
15 concentrations on substrate material proximate the first surface.
11. (Original) The method of claim 10, wherein said act of forming comprises  
forming two terminal regions with the central region interposed therebetween.
- 20 12. (Original) The method of claim 10, wherein said act of forming comprises  
forming at least one terminal region which is generally elliptical when viewed  
from above the first surface.

Reply to office action dated 12/14/04

13. (Original) A print cartridge comprising, at least in part, a substrate formed in accordance with the method of claim 10.

5 14. (Currently amended) A method comprising:

forming a fluid-feed slot by removing substrate material between a first substrate surface and a second generally opposing substrate surface, the fluid-feed slot extending along a long axis which lies generally parallel to the first substrate surface, the fluid-feed slot having a cross-section at the first surface and  
10 taken generally parallel the first surface comprising a narrower central region positioned between two wider terminal regions; and,

rounding the slot at the first surface by removing additional substrate material, at least in part, to decrease stress concentrations on substrate material proximate the first surface.

15

15. (Original) The method of claim 14, wherein said act of rounding comprises contacting substrate material with a drill bit.

16. (Original) A method comprising:

20 forming a slot into a substrate between a first substrate surface and a second generally opposing substrate surface; and,  
rounding a region where the slot intersects the first surface.

Reply to office action dated 12/14/04

17. (Original) The method of claim 16, wherein said act of forming occurs prior to said act of rounding.

5 18. (Currently amended) The method of claim 16, wherein said act of forming a slot comprises forming a slot extending along a long axis that extends generally parallel to the first surface and having a central region and at least one terminal region arranged along the long axis.

10 19. (Currently amended) The method of claim 16, wherein said act of forming a slot comprises forming a slot extending along a long axis that extends generally parallel to the first surface and having a central region interposed between two bowl-shaped terminal regions arranged generally along the long axis wherein each of the terminal regions has a width at the first surface taken generally  
15 orthogonal to the long axis that is greater than a width of the central region at the first surface taken generally orthogonal to the long axis.

20. (Currently amended) A method comprising:

forming a central region of a slot into a semiconductor substrate the  
20 central region extending between a first substrate surface and a generally opposing second substrate surface; and,

Reply to Office action dated 12/14/04

forming two terminal regions of the slot into the first surface generally  
contiguous with and interposed by the central region, each of the two terminal  
regions having a width at the first surface taken generally orthogonal to a long  
axis of the slot that is greater than a width of the central region at the first surface  
5 taken generally orthogonal to the long axis of the slot where the long axis does  
not intersect the first substrate surface.

21. (Original) The method of claim 20, wherein said act of forming two  
terminal regions comprises forming two terminal regions which do not extend to  
10 the second surface of the substrate.

22. (Original) The method of claim 20, wherein said act of forming two  
terminal regions comprises forming two terminal regions which extend through  
less than a majority of a thickness of the substrate as defined between the first  
15 and second surfaces.

23. (Original) The method of claim 20, wherein said act of forming two  
terminal regions comprises forming two terminal regions which are generally  
circular when viewed from above the first surface.  
20

24. (Original) The method of claim 20, wherein said act of forming the central  
region comprises rounding the central region into the first surface and wherein

Reply to Office action dated 12/14/04

said act of forming two terminal regions comprises rounding the two terminal regions into the first surface.

25. (Original) The method of claim 20 further comprising forming two  
5 additional terminal regions into the second surface which are contiguous with  
and interposed by the central region.